

Capabilities & Equipment

Full Service Tool Room

- (8) Bridgeport EZ-Trak SX mills
- 2D CNC / manual

- Amada Meister V3 CNC surface and form grinder
- 6" x 18" table
 - 2 axes plus table axis
 - 10 wheel management system

- (10) Surface grinders
- Maximum table size: 16" x 32"

Moore Model G18 jig grinder

- (5) Drill presses • Maximum radial arm length: 4'

Part Cleaning

- Aquamaster Conveyorized Parts Cleaner CB-1200E
- 12 x 12" capacity

- Crystal Clean Heated Aqueous Parts Cleaner
- 24 x 24 x 4.5" capacity

- Apex 2052M-DSSDC Deburring Machine
- Max Part Width: 52"

Wire EDM

- (2) Agiecut Progress VP3
- Maximum Travel: 19.68" (X) x 13.77" (Y) x 16.77" (Z)
 - Maximum Work piece: 41.3" x 26.6" x 16.77" high
 - Minimum wire diameter: .006"
 - Achievable tolerance: < .0001"

- (2) Agiecut Progress VP2
- Maximum Travel: 13.77" (X) x 9.84" (Y) x 10.87" (Z)
 - Maximum Work piece: 29.52" x 21.65" x 9.84" high
 - Minimum wire diameter: .003"
 - Achievable tolerance: < .0001"

- Sodick K1C hole drilling EDM
- Hole diameter range: .012" - .120"

- All wire EDMs cut fully submersed and feature automatic threading
- EDM room is climate controlled

CAD / CAM Software

Solidworks
LogoPress 3
AutoCAD with Diemaker
FASTFORM
DRBLANK
GibbsCAM
Esprit

Fabrication

- (2) Trumpf 5030 Fiber Lasers - TruFlow 5000 watt laser
- Max sheet 60" x 120"
 - Auto loading/unloading for unattended operation
 - cuts 3x faster than Co2 in materials under 3/8" thick

- Trumpf TruPunch 1000 punching machine
- Maximum punching force: 20 tons
 - Maximum punching rate: 600 SPM
 - Maximum sheet size: .250" x 48" x 120"

- Safan 300-4100, High speed electric brake press
- Press capacity: 330 tons x 161" length capacity
 - Auto sheet thickness measuring and 6-axis back gauging

- Trumpf TruBend 5085 CNC press brake
- Press capacity: 85 tons x 87" bending length

- Bystronic, Xpert 40 high speed brake
- Press capacity: 44 tons x 40" bending length
 - 3X faster working speed than other hydraulic brakes

- Bystronic, Xact Smart 160 high speed brake
- Press capacity: 160 tons x 120" bending length

- 9 Welding Bays
- Lincoln Wire-Matic 140 & 250 welder
 - Lincoln Square Wave TIG 355 welder
 - Federal 100 KVA Spot Welder / 30" throat

- Americor Plate Roller - 5' x 10 ga capacity
Timesaver deburring - 36" wide capacity
(2) Haeger HP-6 hardware insertion press Auto-feeder
Haeger 824 OneTouch-5e 2 Bowl Pem Machine
Assembly & Testing stations
Overhead crane capacity 5 tons
Forklift capacity 5,000 lbs.

Capabilities & Equipment

Metal Stamping

200 ton Komatsu OBW gap frame press*

- Bolster: 33" x 95" - SPM: 0 to 50
- Maximum stock: 18" x .187" thick

175 ton Bliss SG2 straight side press*

- Bolster: 30" x 84" - SPM: 30 to 60

100 ton Minster Piece-Maker straight side press*

- Bolster: 31" x 48" - SPM: 0 to 120
- Maximum stock: 12" wide x .130" thick

100 ton Minster Piece-Maker straight side press*

- Bolster: 31" x 60" SPM: 0 to 250
- Maximum stock: 14" wide x .240" thick

100 ton Bliss*

80 ton Minster OBI press

75 ton Bliss C2 single stroke gap frame press*

60 ton Minster with 2" stroke, up to 400 SPM*

30 ton Bruderer BSTA30 press*

Multiple air presses ranging 6-12 tons

*All presses include press automation, die protection and automatic coil feed line

Quality Assurance

Keyence Image Dimension Measuring System IM-7030

SmartScope Flash 200 video measuring machine

- Measuring range: 8" x 8" x 6"
- Accuracy to < .0001" (3.2 microns)

Brown & Sharpe FX7107 Global automatic CMM

- PC DMIS 4.3 software
- Measuring range: 25" x 39" x 25"

Brown & Sharpe Micro Excel 765 CMM

- Measuring range: 30" x 26" x 20"

Virtek Laser QC 1200

- Measuring range: 8" x 48" x 48"

Romer Arm Model 7540

- Measuring range: 13.1 feet

Hexagon's Global FX 7107 CMM

(3) Optical Comparators

Mitutoyo LH600 Computerized Linear Height Gage 24"

Imada ZTS-550 Digital Force Gauge

CNC Machining

Kitamura HX400iG/500 CNC Horizontal 4-Axis machining center

- 400mm Pallet
- Travel 24" (X) x 24" (Y) x 24" (Z)

OKK HM500S CNC Horizontal 4-Axis Machining Center

- Travel: 24.8" (X) x 24.41" (Y) x 27.95" (Z)
- 500mm Pallet

(2) Robo Drill D21LiA5

- Travel: 27.5" (X) x 15.7" (Y) x 13.00" (Z)
- 24,000 RPM Spindle
- 21 tool magazine

Brother S1000X1

- Travel: 39.4" (X) x 19.685" (Y) x 11.8" (Z)
- 21 tool magazine

(2) OKK VM5 CNC Vertical Machining Centers

- Travel: 40" (X) x 20" (Y) x 20" (Z)
- 20 tool magazine, 50 Taper

(3) Hurco Vertical Machining Centers

- Travel up to 64" (X) x 34" (Y) x 30" (Z)
- 4-Axis option's

(2) Haas VF2YT

- Travel: 30" (X) x 20" (Y) x 20" (Z)
- 40 tool magazine

(2) Haas VF-5SS

- Travel: 50" (X) x 26" (Y) x 25" (Z)
- 50+1 tool capacity
- TR210, 5 axis trunnion

CNC Turning

Eurotech B438 Rapido Sub-Spindle lathe with live tooling

- Dual turrets with Y-axis travel
- 1.50" Bar capacity

Hyundai LM1800TTSY CNC lathe with 2.6" bar feeder

- Sub-spindle lathe with live tooling and Y-axis travel
- Maximum length: 26.5"

(4) Samsung CNC Lathes

- Up to 3.00" bar feeder
- Live tooling